



## GSZ 4-280 EL

### Straight grinder 28 000/min

Extremely ergonomic die grinder with high plunge depth for light grinding and deburring in especially difficult-to-reach spots.

Product number: 7 223 24 60 00 0

## Details

- + Long narrow neck and maximum diameter of 210 mm allows tool to plunge a long way into workpieces (e.g. grinding inside pipes).
- + Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes.
- + Variable speed allows different tools to be used.
- + Motor and electronics protected against metal dust.
- + Removable rubber collar bearing cover.

## Price includes

- + 1 collet Ø 6 mm
- + Jaw spanner SW17
- + Jaw spanner SW13

## Product feature

- + Long neck

## Application



Cutting	++
Roughing-down	++
Grinding	++
Deburring	+
Brushing	+

+ suitable  
 ++ well suitable

## Technical data

### TECHNICAL DATA

Input	350 W
Output	170 W
Speed, no load	13,000 - 28,000 rpm
Grinding wheel for max. Ø	20 mm
Collet for max. Ø	6 mm
Collar Ø	43 mm
Max. cutter diameter	12 mm
Cable with plug	5 m
Weight according to EPTA	1.50 kg

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	83,2 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	91,2 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	96,3 dB 3 dB
Vibration value 1 $\alpha_{hv}$ 3-way Uncertainty of measured value K $\alpha$	4,8 m/s <sup>2</sup> 1,5 m/s <sup>2</sup>

## Application examples



**FEIN**

