

HEAMAR COMPANY

PRECISION WIRE STRIPPERS

www.heamar.co.uk

IDEAL Custom Stripmaster



- Die-type blades allow for precision stripping.
- Contains counterbored hole sized to the insulation and inner stripping hole sized to the conductor.
- The counterbored hole centres the conductor and prevents the blade from contacting the surface of the conductor.
- Die-type blades are manufactured to assure accuracy and precision to meet tough MIL-Specs.
- Custom Stripmaster Lite versions are available.

WIRE SPECIFICATION	HAND TOOL	BLADE ONLY	WIRE RANGE AWG
AD, DR	45-2825 45-2824	45-2825-1 45-2824-1	10-14 16-26
BMS 13-48 TYPES 1-7, 25, 26, 30 (6 mil wall thickness)	45-2500 45-1551	45-2500-1 45-1551-1	10-14 16-26
BMS 13-48 TYPES 10-14, 27, 28, 31, 32, 35, 36 (8 mil wall thickness)	45-1611 45-1654	45-1611-1 45-1654-1	10-14 16-26
BMS 13-48 TYPES 8, 9, 15, 23, 24 (10 mil wall thickness)	45-1611 45-1987	45-1611-1 45-1987-1	10-14 16-26
BMS 13-60 TYPES 1-6, 19-21, 23-27, 33-34	45-2541 45-2543	45-2541-1 45-2543-1	10-14 16-24
BMS 13-60 TYPES 12-18, 28-32	45-2542 45-2544	45-2542-1 45-2544-1	10-14 16-24
BMS 13-60 TYPES 7-12	45-2565 45-2564	45-2565-1 45-2564-1	10-14 16-26
BMS 13-60 TYPES 13-18, 28-32	45-2686	452686-1	16-24
Raychem 44A01XX, 44/04XX & 55A081X	45-1611 45-1987 45-178M	45-1611-1 45-1987-1 L-5561	10-14 16-26 26-30
Raychem 55A011X	45-178M	L-5561	26-30
Raychem 55M011X	45-1774	45-1774-1	12-14
Raychem 55M081X	45-1773	45-1773-1	16-26
Raychem 99M0111	45-1928M 45-1927M	45-1928-1 45-1927-1	12-14 16-26

More models, parts and accessories for the **IDEAL Custom Stripmaster** and **IDEAL Ergo Elite** are available.

Please visit our website, www.heamar.co.uk, or contact us for more information.

HEAMAR COMPANY

PRECISION WIRE STRIPPERS

www.heamar.co.uk

IDEAL Ergo Elite



- Ergonomically engineered for superior comfort, balance and control reducing the risk of repetitive strain injury.
- The light-weight Ergo Elite is constructed at 40% the weight of the original metal hand tools.
- Tilted head assembly maintains a neutral wrist allowing an unobstructed view of wire positioning.
- Patented three-piece constructed blade meets military stripping specifications.

WIRE SPECIFICATION	HAND TOOL	BLADE ONLY	WIRE RANGE AWG
BMS 13-48 TYPES 1-7, 25, 26, 30 (6 mil wall thickness)	55-1987	55-1987-1	16-26
BMS 13-48 TYPES 10-14, 27, 28, 31, 32, 35, 36 (8 mil wall thickness)	55-1987	55-1987-1	16-26
BMS 13-48 TYPES 8, 9, 15, 23, 24 (10 mil wall thickness)	55-1987	55-1987-1	16-26
BMS 13-78	55-2933	55-2933-1	16-22
BMS 13-80	55-2934	55-2934-1	22-26
MIL-W-22759/11/12/22/23	55-5560	55-5560-1	16-26
MIL-W-22759/16/17	55-1987	55-1987-1	16-26
MIL-W-22759/32/33/44/45/46	55-1987	55-1987-1	16-26
MIL-W-25038/3	55-2901	55-2901-1	16-22
MIL-W-81044/8/9/10	55-2901	55-2901-1	16-26
MIL-W-81044/11/12/13 MIL-W-22759/34/35/41/42/43	55-1987	55-1987-1	16-26

More models, parts and accessories for the **IDEAL Custom Stripmaster** and **IDEAL Ergo Elite** are available.

Please visit our website, www.heamar.co.uk, or contact us for more information.

HEAMAR COMPANY

PRECISION WIRE STRIPPERS

www.heamar.co.uk

IDEAL Ringer Strippers



- Strip most non-round shielded cable and other outer jackets, including extruded Teflon, Kapton, PVC and Kynar.
- Spring-loaded head holds cable, no need for adjustment.
- Fixed blades are sized to insulation, preventing inaccurate cuts.
- Heat-treated stainless-steel blades assure long life.

PART NUMBER	BLADE INCLUDED	DESCRIPTION
45-401 (Orange)	K-6492	5 mil insulation thickness including Kapton
45-402 (Yellow)	K-6493	8-10 mil insulation thickness including Kynar
45-400 (Blue)	Sold Separately	Cable diameters up to 0.12 inches
45-4003 (Red)	Sold Separately	Cable diameters from 0.12 inches to 0.22 inches
45-404 (Green)	Sold Separately	With "deep-V" for larger cable diameters up to 0.20 inches

Ringer Blades

PART NUMBER	CUTTING DEPTH
K-6499	0.0120 in
K-6500	0.0130 in
K-6501	0.0140 in
K-6502	0.0160 in
K-6503	0.0180 in
K-6504	0.0200 in
K-6505	0.0220 in
K-6491	0.0030 in

PART NUMBER	CUTTING DEPTH
K-6492	0.0044 in
K-6493	0.0060 in
K-6494	0.0070 in
K-6495	0.0080 in
K-6496	0.0090 in
K-6497	0.0100 in
K-6498	0.0110 in

IDEAL Coaxial Cable Strippers



- Lightweight, compact, cost effective stripper. Simple to operate, the adjustable blades can be set for any depth to help ensure nick-free strips.
- Use with twisted-pair wire, tightly wrapped stranded cables, CATV cable, CB antenna cable, SO, SJ, SJT and other types of flexible power cords.
- Blades included, replacements available.

PART NUMBER	BLADE INCLUDED	DESCRIPTION
45-162 (Grey)	RG-174 & RG-187	Coaxial cable stripper up to 1/8 in (3.2mm) O.D.
45-163 (Blue)	RG-58 & CB Antenna Cable	Coaxial cable stripper from 1/8 in (3.22mm) to 7/32 in (5.556mm) O.D.
45-164 (Blue)	RG-8	Coaxial cable stripper from 1/4 in (6.4mm) to 9/16 in (14.3mm) O.D.
45-165 (Black)	RG-59 & UTP Cable	Coaxial cable stripper from 3/16 in (4.8mm) to 5/16 in (8mm) O.D.