

HEAMAR COMPANY

STRIPPING MACHINES

www.heamar.co.uk

IDEAL 45-930 Stripping Machine



- IDEAL Programmable Shielded Twisted Pair cable stripping system meets strict tolerances.
- Hot-blade thermal cable stripping system adjusts to protect shielded cable for accurate stripping every time.
- Automatically adjusts for cable up to 3125 in (7.9mm) diameter.
- Strip lengths are adjustable in inches or millimetres from 1.25 in to 6.00 in (31.7mm to 152.4mm).
- Cycles in as little as six seconds, stores up to 500 batch programmes.

IDEAL 45-950 Stripping Machine



- IDEAL Pneumatic Precision Wire Stripper automatically strips 30 AWG through 10 AWG solid or stranded wire.
- Accomodates six different wire diameters without switching tool or blade sets.
- Electronic triggering for easy and accurate strips.
- Meets military and commercial wire stripping speciifcations.
- Replaceable wire guides and blades for maximum flexibility.
- Controls strip length accurately from 125 in to 0.630 in with individual adjustable strip lengths for each part.

HE Strip Pro Precision Pneumatic Wire Strippers



- A precision, air powered, high volume production tool with the portability of a hand tool, offering exceptional accuracy and dependability for wire harness, bench top and other MIL-Spec or commercial applications.
- Designed for 6-30 AWG wires (6-0.05mm²), including Kapton, Teflon, Tefzel, Fiberglass, Shielded, Coaxial and Fiber Optic cables.
- Self aligning, proprietary blade design with tolerance of +0.0005 in (0.013mm), assures nick-free conductor and square insulation.
- Proprietary circumferencial gripper design eliminates insulation damage and requires minimal wire break out of 15.9mm for stripping wire bundles.
- MIL-Spec approved counterbored die-type blade design.

HE STRIP-PRO for 12-30 AWG wires (4.0 to 0.05mm ² nominal)	
HE-200	Strip length to ¾ in (19mm)
HE-202	Strip length to 2 in (50.8mm)
HE-203	Strip length to 3 in (76.2mm)
HE-200C	Shielded and coaxial cables

HE STRIP-PRO for 6-16 AWG wires (6 to 1.5mm ²)	
HE-220	Strip length to ¾ in (19mm)
HE-220C	Shielded and coaxial cables
HE-230	Heavy duty, 6-10 AWG